

SHELL 9 UP TWIN



PELLET AIR - Pellet stoves

CADEL




Certificate model name : SHELL 3 UP



Nominal power	kW	9,1
Reduced power	kW	2,4
Introduced thermal power (max)	kW	10,3
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Seasonal energy efficiency	ηs [%]	85
Nominal efficiency	%	88,7
Reduced efficiency	%	92,9
Heating volume (min-max)	m³	68 - 259
Nominal CO at 13% O ₂	%	0,005
Reduced CO at 13% O ₂	%	0,022
Emissions CO (13% O ₂) (min-max)	mg/Nm³	274 - 63
Emissions OGC (13% O ₂) (min-max)	mg/Nm³	3,9 - 2,1
Emissions NOX (13% O ₂) (min-max)	mg/Nm³	104 - 139
Dust content at 13% O ₂ (min- max)	mg/Nm³	19,3 - 12,1
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	17
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,53 - 2,12
Autonomy (min-max)	h	8 - 32,1
Ignition electrical absorption (max)	W	346
Operating electrical absorption (max)	W	77
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	11,6
Mass of smoke (min-max)	g/sec	2,2 - 5,0
Exhaust fumes temperature (max)	°C	204,6
Net weight	kg	88
Gross weight	kg	98
Exhaust fumes (A)	Ø mm	80
Hole combustion air inlet (B)	Ø mm	130
Ducting outlet (C)	Ø mm	-
Ducting capability up to	m	-




MATCH

7019018		Anthracite steel	EAN 8053859010777
7019019		White steel	EAN 8053859010784
7019021		Titanium steel	EAN 8053859010807

PLUS

	Cast iron burning pot		Sealed chamber		Aluminium Auger
	Connection to the room thermostat		Comfort mode		Upper exhaust
	Concentric kit		Daily weekly programming		Bluetooth
	Magic Glass		Integrated Wi-Fi		


STOVE PACKING



L (cm)	H (cm)	P (cm)
79	79	130


VOLUME (m³)
0,69

LINING PACKING



	L (cm)	H (cm)	P (cm)
	-	-	-

STOCKING



TRANSPORT

