



LIFE 9

AIR - Pellet stoves

Certificate model name : LIFE 9 T1



| | | |
|---|--------------------|-----------|
| Nominal power | kW | 8,5 |
| Reduced power | kW | 2,5 |
| Introduced thermal power (max) | kW | 9,5 |
| Nominal water useful power | kW | - |
| Reduced water useful power | kW | - |
| Nominal efficiency | % | 89 |
| Reduced efficiency | % | 90 |
| Heating volume (min-max) | m ³ | 70 - 238 |
| Nominal CO at 13% O ₂ | % | 0,013 |
| Reduced CO at 13% O ₂ | % | 0,024 |
| Emissions CO (13% O ₂) (min-max) | mg/Nm ³ | 297 - 160 |
| Emissions OGC (13% O ₂) (min-max) | mg/Nm ³ | 5 - 3 |
| Emissions NOX (13% O ₂) (min-max) | mg/Nm ³ | 120 - 130 |
| Dust content at 13% O ₂ (min-max) | mg/Nm ³ | 20 - 15 |
| Boiler capacity (H ₂ O) | l | - |
| Hopper capacity | kg | 17 |
| Combustible | | Pellet ø6 |
| Hourly consumption (min-max) | kg/h | 0,6 - 2,0 |
| Autonomy (min-max) | h | 8 - 28 |
| Ignition electrical absorption (max) | W | 340 |
| Operating electrical absorption (max) | W | 96 |
| Supply and frequency | V - Hz | 230 - 50 |
| Chimney flue depression | Pa | 10 |
| Exhaust diameter | mm | 80 |
| Combustion air inlet diameter | mm | 50 |
| Mass of smoke (min-max) | g/sec | 3,1 - 6,0 |
| Exhaust fumes temperature (max) | °C | 196 |
| Net weight | kg | 79 |
| Gross weight | kg | 89 |
| Exhaust fumes | see | A |
| Hole combustion air inlet | see | B |
| Ducting outlet | see | - |
| Ducting capability up to | m | - |



Art. 15A-B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



MATCH

| | | | |
|---------|--|-----------------|-------------------|
| 7022021 | | Black steel | EAN 8053859014898 |
| 7022022 | | Titanium steel | EAN 8053859014904 |
| 7022023 | | Dark gold steel | EAN 8053859014911 |

PLUS



AIRTIGHT sealed chamber



Integrated Wi-Fi



Easy start



Connection to the room thermostat



Back exhaust



Cast iron burning pot



Silent function




Daily weekly programming



DUO-SHIELD combustion chamber


STOVE PACKING



| L (cm) | H (cm) | P (cm) |
|--------|--------|--------|
| 79 | 120 | 60 |


| | |
|--------------------------|------|
| VOLUME (m ³) | 0,57 |
|--------------------------|------|

LINING PACKING



| | L (cm) | H (cm) | P (cm) |
|-------|--------|--------|--------|
| steel | - | - | - |

STOCKING



TRANSPORT

