







Nominal power	kW	11
Reduced power	kW	3,3
Introduced thermal power (max)	kW	12,1
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	91
Reduced efficiency	%	93,5
Heating volume (min-max)	m ³	79 - 264
Nominal CO at 13% O ₂	%	0,0022
Reduced CO at 13% O ₂	%	0,022
Emissions CO (13% O ₂) (min-max)	mg/Nm ³	268 - 27
Emissions OGC (13% O ₂) (min-max)	mg/Nm ³	7,0 - 2,0
Emissions NOX (13% O ₂) (min-max)	mg/Nm ³	105 - 119
Dust content at 13% O ₂ (min-max)	mg/Nm ³	11 - 14
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	22
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,73 - 2,6
Autonomy (min-max)	h	8,5 - 30
Ignition electrical absorption (max)	W	360
Operating electrical absorption (max)	W	137,3
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	10
Exhaust diameter	mm	80
Combustion air inlet diameter	mm	60
Mass of smoke (min-max)	g/sec	3,7 - 7,1
Exhaust fumes temperature (max)	°C	174
Net weight	kg	98
Gross weight	kg	108
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-
Ducting capability up to	m	-



Art. 15A B-VG 2015
BImSchV 2016
Regensburg
München
Stuttgart
Aachen



MATCH

7017067		White steel	EAN 8033123618809
7017068		Moka steel	EAN 8033123618816
7017069		Anthracite steel	EAN 8033123618823

PLUS



AIRTIGHT Sealed chamber



Wi-Fi kit (optional)



Easy start



Remote control **



Lateral exhaust



Cast iron burning pot



Silent function



Connection to the room thermostat




Daily weekly programming



Upper exhaust (optional)

** Operation requires 1 CR 2025 Lithium battery.
Used batteries contain metals which are harmful for the environment; they must therefore be disposed of separately in the special containers.


STOVE PACKING



L (cm)	H (cm)	P (cm)
80	124,5	70


VOLUME (m ³)
0,70

LINING PACKING



	L (cm)	H (cm)	P (cm)

STOCKING



TRANSPORT

