



CHROME 5 AIRTIGHT

AIR - Pellet stoves



Nominal power	kW	5,5
Reduced power	kW	2,5
Introduced thermal power (max)	kW	6,1
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	90
Reduced efficiency	%	91
Heating volume (min-max)	m ³	55 - 132
Nominal CO at 13% O ₂	%	0,011
Reduced CO at 13% O ₂	%	0,019
Emissions CO (13% O ₂) (min-max)	mg/Nm ³	238 - 140
Emissions OGC (13% O ₂) (min-max)	mg/Nm ³	4 - 2
Emissions NOX (13% O ₂) (min-max)	mg/Nm ³	140 - 129
Dust content at 13% O ₂ (min-max)	mg/Nm ³	20 - 15
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	11
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,6 - 1,3
Autonomy (min-max)	h	8,5 - 18,3
Ignition electrical absorption (max)	W	345
Operating electrical absorption (max)	W	49
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	10
Exhaust diameter	mm	80
Combustion air inlet diameter	mm	130
Mass of smoke (min-max)	g/sec	2,6 - 3,9
Exhaust fumes temperature (max)	°C	149
Net weight	kg	73
Gross weight	kg	83
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-
Ducting capability up to	m	-



Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



MATCH

7021016		Black steel	EAN 8053859013266
7021017		Titanium steel	EAN 8053859013273
7021018		Dark gold steel	EAN 8053859013280

PLUS



AIRTIGHT Sealed chamber



Integrated Wi-Fi



Easy start



Remote control **



DUO-SHIELD combustion chamber



Cast iron burning pot



Silent function



Connection to the room thermostat




Daily weekly programming



Upper exhaust

** Operation requires 1 CR 2025 Lithium battery.
Used batteries contain metals which are harmful for the environment; they must therefore be disposed of separately in the special containers.


STOVE PACKING



L (cm)	H (cm)	P (cm)
80	114,3	60


VOLUME (m ³)
0,55

LINING PACKING



	L (cm)	H (cm)	P (cm)
steel	50	6	50

STOCKING



TRANSPORT

