

SWEET 7




PELLET AIR - Pellet stoves

CADEL

Certificate model name : SWEET 7 T2



Nominal power	kW	7
Reduced power	kW	2,9
Introduced thermal power (max)	kW	7,9
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Seasonal energy efficiency	ηs [%]	85
Nominal efficiency	%	89
Reduced efficiency	%	90
Heating volume (min-max)	m³	83 - 200
Nominal CO at 13% O ₂	%	0,0018
Reduced CO at 13% O ₂	%	0,010
Emissions CO (13% O ₂) (min-max)	mg/Nm³	220 - 125
Emissions OGC (13% O ₂) (min-max)	mg/Nm³	2 - 2
Emissions NOX (13% O ₂) (min-max)	mg/Nm³	110 - 99
Dust content at 13% O ₂ (min- max)	mg/Nm³	15 - 15
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	15
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,6 - 1,7
Autonomy (min-max)	h	25 - 8,8
Ignition electrical absorption (max)	W	350
Operating electrical absorption (max)	W	74
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	11
Mass of smoke (min-max)	g/sec	3 - 5
Exhaust fumes temperature (max)	°C	185
Net weight	kg	56
Gross weight	kg	66
Exhaust fumes (A)	Ø mm	80
Hole combustion air inlet (B)	Ø mm	60
Ducting outlet (C)	Ø mm	-
Ducting capability up to	m	-



Art. 15A-B-VG 2015
BimSchV 2015
Regensburg
München
Stuttgart
Aachen



MATCH

7024030	Anthracite steel	EAN 8053859020882
7024028	White steel	EAN 8053859020868
7024029	Red steel	EAN 8053859020875

PLUS



Sealed chamber



Daily weekly programming



5 stars



Cast iron burning pot



Back exhaust



Bluetooth+
Integrated Wi - Fi



Connection to the
room thermostat




Shield



Comfort mode


STOVE PACKING



L (cm)	H (cm)	P (cm)
79	110.8	60

VOLUME (m³)
0,53

LINING PACKING




L (cm)	H (cm)	P (cm)

STOCKING



Nr (max)
2

TRANSPORT



66 pcs