

EOS 8




AIR PLUS - Ducted pellet stoves



Certificate model name: EOS 8 T1



Nominal power	kW	8,5
Reduced power	kW	3,2
Introduced thermal power (max)	kW	9,4
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Seasonal energy efficiency	ηs [%]	87
Nominal efficiency	%	90
Reduced efficiency	%	90
Heating volume (min-max)	m³	90 - 238
Nominal CO at 13% O ₂	%	0,010
Reduced CO at 13% O ₂	%	0,013
Emissions CO (13% O ₂) (min-max)	mg/Nm³	163 - 125
Emissions OGC (13% O ₂) (min-max)	mg/Nm³	1 - 1
Emissions NOX (13% O ₂) (min-max)	mg/Nm³	110 - 100
Dust content at 13% O ₂ (min-max)	mg/Nm³	15 - 15
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	19
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0,7 - 1,9
Autonomy (min-max)	h	27 - 10
Ignition electrical absorption (max)	W	370
Operating electrical absorption (max)	W	110
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	11
Mass of smoke (min-max)	g/sec	3,6 - 5,3
Exhaust fumes temperature (max)	°C	180
Net weight	kg	100
Gross weight	kg	110
Exhaust fumes (A)	Ø mm	80
Hole combustion air inlet (B)	Ø mm	130
Ducting outlet (C)	Ø mm	80
Ducting capability up to	m	6



Art. 15A-B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



MATCH

7024001



Black steel

EAN 8053859020455

PLUS



Airtight pellet stove



Integrated Wi-Fi + Bluetooth



Living fire round cast iron brazier



Easy start brazier



Daily weekly programming



Integrated temperature sensor



Connection to the external thermostat



Silent



Back exhaust



Ceramic glow plug



Cast iron combustion chamber




Smart Heat



UPS ready


STOVE PACKING



L (cm)	H (cm)	P (cm)
79	126	67


VOLUME (m ³)
0.67

LINING PACKING



L (cm)	H (cm)	P (cm)

STOCKING



TRANSPORT

