

Models	ATRIUM 5 AIRTIGHT
Intended use of the product:	Mechanically by wood pellets fed roomheater
Manufacturer	Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia
Mark	FREEPOINT
AVCP system	System 3
Notified body	NB 0051
Test report number	CS20-0048554-01
Harmonised technical specification	EN 14785:2006

**ESSENTIAL CHARACTERISTICS**

<b>Stability and mechanical resistance</b>	Load bearing capacity	20 kg	
<b>Fire safety - protection of combustible materials</b>	Minimum distance to combustible materials - bottom (dB)	0 mm	
	Minimum distance to combustible materials - front floor (dF)	0 mm	
	Minimum distance to combustible materials - ceiling (dC)	750 mm	
	Minimum distance to combustible materials - rear (dR)	40 mm	
	Minimum distance to combustible materials - side (dS)	250 mm	
	Minimum distance to combustible materials - lateral radiation (dL)	0 mm	
	Minimum distance to combustible materials - frontal radiation (dP)	600 mm	
	Thickness of protective insulating material	/	
	Thermal conductivity of protective insulating material ( $\lambda_d$ )	/	
	Flue temperature class	T200G	
<b>Performance - Emissions</b>	No	Nominal power	Potenza ridotta
	Carbon monoxide emissions (CO at 13% O <sub>2</sub> )	141 mg/Nm <sup>3</sup>	235 mg/Nm <sup>3</sup>
	Emission of nitrogen oxides (NOX at 13% O <sub>2</sub> )	123 mg/Nm <sup>3</sup>	121 mg/Nm <sup>3</sup>
	Emission of organic gaseous compounds (OGC at 13% O <sub>2</sub> )	4 mg/Nm <sup>3</sup>	7 mg/Nm <sup>3</sup>
	Particulate matter emissions (PM at 13% O <sub>2</sub> )	17 mg/Nm <sup>3</sup>	20 mg/Nm <sup>3</sup>
<b>Performance - Power and efficiency</b>	Heating power to the environment	5.2 kW	2.5 kW
	Heating power to the water	/	/
	Efficiency - Useful efficiency	89 %	91 %
<b>Safe and accessible use - chimney installation data</b>	Flue gas outlet temperature	200 °C	138 °C
	Minimum flue draught	10 Pa	10 Pa
	Flue gas mass flow	4.1 g/sec	2.7 g/sec
<b>Energy efficiency index</b>	Seasonal energy efficiency	85 ηs [%]	
	Energy efficiency index	125	
	Energy efficiency class (A++ / G scale)	A+	
	Electrical consumption at nominal heat output	62 W	
	Electrical consumption at partial load heat output	15 W	
	Electrical consumption in standby mode	1.7 W	
<b>Sustainable use of natural resources</b>	Environmental sustainability information	NPD	

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the responsibility of the manufacturer identified above.

Santa Lucia di Piave, 05/03/20

**CADEL s.r.l.**  
 Via Martiri della Libertà, 74  
 31025 SANTA LUCIA DI PIAVE (TV)  
 Tel. 0438 1520200 - Fax 0438.793443  
 Partita IVA 05210270265  
 R.E.A. TV 227665 - Reg. Soc. Trib. TV 188948

Dassie Roberto (R&D Manager)