

|                                    |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| Models                             | DUNE 9 K1                                                                         |
| Intended use of the product:       |                                                                                   |
| Manufacturer                       | Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia |
| Mark                               | CADEL                                                                             |
| AVCP system                        | System 3                                                                          |
| Notified body                      | NB 0051                                                                           |
| Test report number                 | CS26-0136975-01                                                                   |
| Harmonised technical specification | EN 16510-1:2022 / EN 16510-2-6:2022                                               |

### ESSENTIAL CHARACTERISTICS

|                                                            |                                                                        |                        |                        |
|------------------------------------------------------------|------------------------------------------------------------------------|------------------------|------------------------|
| <b>Stability and mechanical resistance</b>                 | Load bearing capacity                                                  | 20 kg                  |                        |
| <b>Fire safety - protection of combustible materials</b>   | Minimum distance to combustible materials - bottom (dB)                | 0 mm                   |                        |
|                                                            | Minimum distance to combustible materials - front floor (dF)           | 300 mm                 |                        |
|                                                            | Minimum distance to combustible materials - ceiling (dC)               | 750 mm                 |                        |
|                                                            | Minimum distance to combustible materials - rear (dR)                  | 150 mm                 |                        |
|                                                            | Minimum distance to combustible materials - side (dS)                  | 200 mm                 |                        |
|                                                            | Minimum distance to combustible materials - lateral radiation (dL)     | 0 mm                   |                        |
|                                                            | Minimum distance to combustible materials - frontal radiation (dP)     | 500 mm                 |                        |
|                                                            | Thickness of protective insulating material                            | /                      |                        |
|                                                            | Thermal conductivity of protective insulating material ( $\lambda_d$ ) | /                      |                        |
|                                                            | Flue temperature class                                                 | T200G                  |                        |
| <b>Performance - Emissions</b>                             |                                                                        | Nominal power          | Reduced power          |
|                                                            | Carbon monoxide emissions (CO at 13% O2)                               | 159 mg/Nm <sup>3</sup> | 230 mg/Nm <sup>3</sup> |
|                                                            | Emission of nitrogen oxides (NOX at 13% O2)                            | 100 mg/Nm <sup>3</sup> | 130 mg/Nm <sup>3</sup> |
|                                                            | Emission of organic gaseous compounds (OGC at 13% O2)                  | 1 mg/Nm <sup>3</sup>   | 3 mg/Nm <sup>3</sup>   |
|                                                            | Particulate matter emissions (PM at 13% O2)                            | 7 mg/Nm <sup>3</sup>   | 20 mg/Nm <sup>3</sup>  |
| <b>Performance - Power and efficiency</b>                  | Heating power to the environment                                       | 8,5 kW                 | 3,2 kW                 |
|                                                            | Heating power to the water                                             | /                      | /                      |
|                                                            | Efficiency - Useful efficiency                                         | 90 %                   | 90 %                   |
| <b>Safe and accessible use - chimney installation data</b> | Flue gas outlet temperature                                            | 200 °C                 | 121 °C                 |
|                                                            | Flue gas mass flow                                                     | 5,4 g/sec              | 3,6 g/sec              |
|                                                            | Draught                                                                | 12 Pa                  | 10 Pa                  |
|                                                            | Draught for chimney sizing calculation (EN13384-1)                     | 2 Pa                   |                        |
| <b>Energy efficiency index</b>                             | Seasonal energy efficiency                                             | 86 ηs [%]              |                        |
|                                                            | Energy efficiency index                                                | 127                    |                        |
|                                                            | Energy efficiency class (A++ / G scale)                                | A+                     |                        |
|                                                            | Electrical consumption at nominal heat output                          | 112 W                  |                        |
|                                                            | Electrical consumption at partial load heat output                     | 38 W                   |                        |
|                                                            | Electrical consumption in standby mode                                 | 2,0 W                  |                        |
| <b>Sustainable use of natural resources</b>                | Environmental sustainability information                               | NPD                    |                        |

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the responsibility of the manufacturer identified above.

Santa Lucia di Piave, 01/07/26

**CADEL s.r.l.**  
Via Martiri della Libertà, 74  
31025 SANTA LUCIA DI PIAVE (TV)  
Tel. 0438 1520200 - Fax 0438.73343  
Partita IVA 03210210266  
R.E.A. TV 227665 - Reg. Soc. Trib. TV 189948

Dassie Roberto (R&D Manager)