

Models	MITHOS PLUS 12 PS T2
Intended use of the product:	Mechanically by wood pellets fed roomheater
Manufacturer	Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia
Mark	CADEL
AVCP system	System 3
Notified body	NB 0051
Test report number	CS23-0095577-01
Harmonised technical specification	EN 14785:2006

## ESSENTIAL CHARACTERISTICS

<b>Stability and mechanical resistance</b>	Load bearing capacity	20 kg	
<b>Fire safety - protection of combustible materials</b>	Minimum distance to combustible materials - bottom (dB)	0 mm	
	Minimum distance to combustible materials - front floor (dF)	1000 mm	
	Minimum distance to combustible materials - ceiling (dC)	750 mm	
	Minimum distance to combustible materials - rear (dR)	200 mm	
	Minimum distance to combustible materials - side (dS)	300 mm	
	Minimum distance to combustible materials - lateral radiation (dL)	100 mm	
	Minimum distance to combustible materials - frontal radiation (dP)	1000 mm	
	Thickness of protective insulating material	/	
	Thermal conductivity of protective insulating material ( $\lambda_d$ )	/	
	Flue temperature class	T200G	
<b>Performance - Emissions</b>	No	Nominal power	Potenza ridotta
	Carbon monoxide emissions (CO at 13% O2)	125 mg/Nm <sup>3</sup>	140 mg/Nm <sup>3</sup>
	Emission of nitrogen oxides (NOX at 13% O2)	99 mg/Nm <sup>3</sup>	120 mg/Nm <sup>3</sup>
	Emission of organic gaseous compounds (OGC at 13% O2)	2 mg/Nm <sup>3</sup>	10 mg/Nm <sup>3</sup>
	Particulate matter emissions (PM at 13% O2)	15 mg/Nm <sup>3</sup>	17 mg/Nm <sup>3</sup>
<b>Performance - Power and efficiency</b>	Heating power to the environment	12 kW	3.7 kW
	Heating power to the water	/	/
	Efficiency - Useful efficiency	89 %	90 %
<b>Safe and accessible use - chimney installation data</b>	Flue gas outlet temperature	200 °C	107 °C
	Minimum flue draught	12 Pa	11 Pa
	Flue gas mass flow	8.8 g/sec	5.7 g/sec
<b>Energy efficiency index</b>	Seasonal energy efficiency	84 ηs [%]	
	Energy efficiency index	125	
	Energy efficiency class (A++ / G scale)	A+	
	Electrical consumption at nominal heat output	153 W	
	Electrical consumption at partial load heat output	49 W	
	Electrical consumption in standby mode	1.7 W	
<b>Sustainable use of natural resources</b>	Environmental sustainability information	NPD	

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the responsibility of the manufacturer identified above.

Santa Lucia di Piave, 24/10/23

**CADEL s.r.l.**  
 Via Martiri della Libertà, 74  
 31025 SANTA LUCIA DI PIAVE (TV)  
 Tel. 0438 1520200 Fax 0438.733443  
 Partita IVA 04621021206  
 R.E.A. TV 227665 - Reg. Soc. Trib. TV 188948

Dassie Roberto (R&D Manager)