

|                                    |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| Models                             | SOUND 7 UP-TWIN T2                                                                |
| Intended use of the product:       | Mechanically by wood pellets fed roomheater                                       |
| Manufacturer                       | Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia |
| Mark                               | CADEL                                                                             |
| AVCP system                        | System 3                                                                          |
| Notified body                      | NB 0051                                                                           |
| Test report number                 | CS25-0115071-02                                                                   |
| Harmonised technical specification | EN 16510-1:2022 / EN 16510-2-6:2022                                               |

### ESSENTIAL CHARACTERISTICS

|                                                            |                                                                        |                        |                        |
|------------------------------------------------------------|------------------------------------------------------------------------|------------------------|------------------------|
| <b>Stability and mechanical resistance</b>                 | Load bearing capacity                                                  | 20 kg                  |                        |
| <b>Fire safety - protection of combustible materials</b>   | Minimum distance to combustible materials - bottom (dB)                | 0 mm                   |                        |
|                                                            | Minimum distance to combustible materials - front floor (dF)           | 0 mm                   |                        |
|                                                            | Minimum distance to combustible materials - ceiling (dC)               | 750 mm                 |                        |
|                                                            | Minimum distance to combustible materials - rear (dR)                  | 200 mm                 |                        |
|                                                            | Minimum distance to combustible materials - side (dS)                  | 300 mm                 |                        |
|                                                            | Minimum distance to combustible materials - lateral radiation (dL)     | 0 mm                   |                        |
|                                                            | Minimum distance to combustible materials - frontal radiation (dP)     | 650 mm                 |                        |
|                                                            | Thickness of protective insulating material                            | /                      |                        |
|                                                            | Thermal conductivity of protective insulating material ( $\lambda_d$ ) | /                      |                        |
|                                                            | Flue temperature class                                                 | T200G                  |                        |
| <b>Performance - Emissions</b>                             | No                                                                     | Nominal power          | Potenza ridotta        |
|                                                            | Carbon monoxide emissions (CO at 13% O2)                               | 125 mg/Nm <sup>3</sup> | 220 mg/Nm <sup>3</sup> |
|                                                            | Emission of nitrogen oxides (NOX at 13% O2)                            | 99 mg/Nm <sup>3</sup>  | 110 mg/Nm <sup>3</sup> |
|                                                            | Emission of organic gaseous compounds (OGC at 13% O2)                  | 2 mg/Nm <sup>3</sup>   | 2 mg/Nm <sup>3</sup>   |
|                                                            | Particulate matter emissions (PM at 13% O2)                            | 15 mg/Nm <sup>3</sup>  | 20 mg/Nm <sup>3</sup>  |
| <b>Performance - Power and efficiency</b>                  | Heating power to the environment                                       | 7 kW                   | 2.9 kW                 |
|                                                            | Heating power to the water                                             | /                      | /                      |
|                                                            | Efficiency - Useful efficiency                                         | 89 %                   | 90 %                   |
| <b>Safe and accessible use - chimney installation data</b> | Flue gas outlet temperature                                            | 239 °C                 | 164 °C                 |
|                                                            | Minimum flue draught                                                   | 11 Pa                  | 11 Pa                  |
|                                                            | Flue gas mass flow                                                     | 5 g/sec                | 3 g/sec                |
| <b>Energy efficiency index</b>                             | Seasonal energy efficiency                                             | 85 $\eta_s$ [%]        |                        |
|                                                            | Energy efficiency index                                                | 125                    |                        |
|                                                            | Energy efficiency class (A++ / G scale)                                | A+                     |                        |
|                                                            | Electrical consumption at nominal heat output                          | 74 W                   |                        |
|                                                            | Electrical consumption at partial load heat output                     | 28 W                   |                        |
|                                                            | Electrical consumption in standby mode                                 | 2.1 W                  |                        |
| <b>Sustainable use of natural resources</b>                | Environmental sustainability information                               | NPD                    |                        |

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the responsibility of the manufacturer identified above.

Santa Lucia di Piave, 16/07/25

**CADEL s.r.l.**  
Via Martiri della Libertà, 74  
31025 SANTA LUCIA DI PIAVE (TV)  
Tel. 0438 1520200 - Fax 0438 733443  
Partita IVA 04621021206  
R.E.A. TV 227665 - Reg. Soc. Trib. TV 188949

Dassie Roberto (R&D Manager)