

INFORMATION REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATIONS (EU) 2015/1185 - (EU) 2015/1186 (PRODUCT FICHE)

Models	CRISTAL 7 T2
Intended use of the product:	Mechanically by wood pellets fed roomheater
Manufacturer	Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia
Trade mark	CADEL
AVCP system	System 3
Notified body	NB 0051
Test report number	CS25-0115071-03
Harmonised technical specification	EN 16510-1:2022 / EN 16510-2-6:2022

ESSENTIAL CHARACTERISTICS

Fuel	Log wood, moisture content $\leq 25\%$			No	
	Compressed wood with moisture content $< 12\%$			Yes	
Type of heat output/room temperature control (select one)	Single stage heat output, no room temperature control			No	
	Two or more manual stages, no room temperature control			No	
	With mechanic thermostat room temperature control			No	
	With electronic room temperature control			No	
	With electronic room temperature control plus day timer			No	
	With electronic room temperature control plus week timer			Yes	
Other control options (multiple selections possible)	Room temperature control, with presence detection			No	
	Room temperature control, with open window detection			No	
	With distance control option			Yes	
Performance - Emissions	No	Symbol		Nominal power	Reduced power
	Carbon monoxide emissions (CO at 13% O ₂)	CO _{nom}	CO _{part}	125 mg/Nm ³	220 mg/Nm ³
	Emission of nitrogen oxides (NOX at 13% O ₂)	NO _{xnom}	NO _{xpart}	99 mg/Nm ³	110 mg/Nm ³
	Emission of organic gaseous compounds (OGC at 13% O ₂)	OGC _{nom}	OGC _{part}	2 mg/Nm ³	2 mg/Nm ³
	Particulate matter emissions (PM at 13% O ₂)	PM _{nom}	PM _{part}	15 mg/Nm ³	20 mg/Nm ³
Performance - Power and efficiency	Heating power to the environment	P _{nom}	P _{part}	7,0 kW	2,9 kW
	Heating power to the water	P _{wnom}	P _{wpart}	/	/
	Efficiency - Useful efficiency	η_{nom}	η_{part}	89 %	90 %
Space heating efficiency	Seasonal energy efficiency	η_s			85 η_s [%]
	Energy efficiency index	EEL			125
	Energy efficiency class (A++ / G scale)	-			A+
Auxiliary electricity consumption	Electrical consumption at nominal heat output	e _{lmax}			0.074 kW
	Electrical consumption at partial load heat output	e _{lmin}			0.028 kW
	Electrical consumption in standby mode	e _{lSB}			0.000 kW
Sealed Chamber	Appliance Type (tightness)	Type			CC50

Observe the specific precautions for installation, assembly and maintenance indicated in the manual accompanying the product, and the national and local rules in force

CADEL s.r.l.
Via Martiri della Libertà, 74
31025 SANTA LUCIA DI PIAVE (TV)
Tel. 0438 1520200 - Fax 0438.73343
Partita IVA 06210210265
R.E.A. TV 227665 - Reg. Soc. Trib. TV 189048

Santa Lucia di Piave, 24/07/25

Dassie Roberto (R&D Manager)