

INFORMATION REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATIONS (EU) 2015/1185 - (EU) 2015/1186 (PRODUCT FICHE)

Models	CRISTAL 9 AIR T1
Intended use of the product:	Mechanically by wood pellets fed roomheater
Manufacturer	Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia
Trade mark	CADEL
AVCP system	System 3
Notified body	NB 1880
Test report number	1880-CPR-043-TR-24
Harmonised technical specification	EN 16510-1:2022 / EN 16510-2-6:2022

ESSENTIAL CHARACTERISTICS

Fuel	Log wood, moisture content $\leq 25\%$	No			
	Compressed wood with moisture content $< 12\%$	Yes			
Type of heat output/room temperature control (select one)	Single stage heat output, no room temperature control	No			
	Two or more manual stages, no room temperature control	No			
	With mechanic thermostat room temperature control	No			
	With electronic room temperature control	No			
	With electronic room temperature control plus day timer	No			
	With electronic room temperature control plus week timer	Yes			
Other control options (multiple selections possible)	Room temperature control, with presence detection	No			
	Room temperature control, with open window detection	No			
	With distance control option	Yes			
Performance - Emissions	No	Symbol		Potenza nominale	Potenza ridotta
	Carbon monoxide emissions (CO at 13% O ₂)	CO _{nom}	CO _{part}	125 mg/Nm ³	163 mg/Nm ³
	Emission of nitrogen oxides (NO _x at 13% O ₂)	NO _{xnom}	NO _{xpart}	100 mg/Nm ³	110 mg/Nm ³
	Emission of organic gaseous compounds (OGC at 13% O ₂)	OGC _{nom}	OGC _{part}	1 mg/Nm ³	1 mg/Nm ³
	Particulate matter emissions (PM at 13% O ₂)	PM _{nom}	PM _{part}	15 mg/Nm ³	15 mg/Nm ³
Performance - Power and efficiency	Heating power to the environment	P _{nom}	P _{part}	8.5 kW	3.2 kW
	Heating power to the water	P _{wnom}	P _{wpart}	/	/
	Efficiency - Useful efficiency	η_{nom}	η_{part}	90 %	90 %
Safe and accessible use - chimney installation data	Flue gas outlet temperature	T _{snom}	T _{spart}	216 °C	121 °C
	Minimum flue draught	p _{nom}	p _{part}	11 Pa	11 Pa
	Flue gas mass flow	$\phi_{f,g nom}$	$\phi_{f,g part}$	5.3 g/sec	3.6 g/sec
Space heating efficiency	Seasonal energy efficiency	η_s	87 η_s [%]		
	Energy efficiency index	EEI	127		
	Energy efficiency class (A++ / G scale)	-	A+		
Auxiliary electricity consumption	Electrical consumption at nominal heat output	e _{lmax}	0.110 kW		
	Electrical consumption at partial load heat output	e _{lmin}	0.012 kW		
	Electrical consumption in standby mode	e _{lSB}	0.002 kW		

Observe the specific precautions for installation, assembly and maintenance indicated in the manual accompanying the product, and the national and local rules in force

CADEL S.r.l.
Via Martiri della Libertà, 74
31025 SANTA LUCIA DI PIAVE (TV)
Tel. 0438 1520200 - Fax 0438.73343
Partita IVA 03202180265
R.E.A. TV 227665 - Reg. Soc. Trib. TV 189948

Santa Lucia di Piave, 24/06/25

Dassie Roberto (R&D Manager)