



**INFORMATION REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATIONS (EU) 2015/1185 - (EU) 2015/1186 (PRODUCT FICHE)**

Models	ELANE 9 T1
Intended use of the product:	Mechanically by wood pellets fed roomheater
Manufacturer	Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia
Trade mark	PEGASO
AVCP system	System 3
Notified body	NB 0051
Test report number	CS25-0121437-01
Harmonised technical specification	EN 16510-1:2022 / EN 16510-2-6:2022

**ESSENTIAL CHARACTERISTICS**

<b>Fuel</b>	Log wood, moisture content $\leq 25\%$	No			
	Compressed wood with moisture content $< 12\%$	Yes			
<b>Type of heat output/room temperature control (select one)</b>	Single stage heat output, no room temperature control	No			
	Two or more manual stages, no room temperature control	No			
	With mechanic thermostat room temperature control	No			
	With electronic room temperature control	No			
	With electronic room temperature control plus day timer	No			
	With electronic room temperature control plus week timer	Yes			
<b>Other control options (multiple selections possible)</b>	Room temperature control, with presence detection	No			
	Room temperature control, with open window detection	No			
	With distance control option	No			
<b>Performance - Emissions</b>	No	Symbol		Nominal power	Reduced power
	Carbon monoxide emissions (CO at 13% O <sub>2</sub> )	CO <sub>nom</sub>	CO <sub>part</sub>	160 mg/Nm <sup>3</sup>	297 mg/Nm <sup>3</sup>
	Emission of nitrogen oxides (NOX at 13% O <sub>2</sub> )	NO <sub>xnom</sub>	NO <sub>xpart</sub>	99 mg/Nm <sup>3</sup>	120 mg/Nm <sup>3</sup>
	Emission of organic gaseous compounds (OGC at 13% O <sub>2</sub> )	OGC <sub>nom</sub>	OGC <sub>part</sub>	3 mg/Nm <sup>3</sup>	5 mg/Nm <sup>3</sup>
	Particulate matter emissions (PM at 13% O <sub>2</sub> )	PM <sub>nom</sub>	PM <sub>part</sub>	15 mg/Nm <sup>3</sup>	20 mg/Nm <sup>3</sup>
<b>Performance - Power and efficiency</b>	Heating power to the environment	P <sub>nom</sub>	P <sub>part</sub>	8,5 kW	2,5 kW
	Heating power to the water	P <sub>wnom</sub>	P <sub>wpart</sub>	/	/
	Efficiency - Useful efficiency	$\eta_{nom}$	$\eta_{part}$	89 %	90 %
<b>Space heating efficiency</b>	Seasonal energy efficiency	$\eta_s$	85 $\eta_s$ [%]		
	Energy efficiency index	EEL	125		
	Energy efficiency class (A++ / G scale)	-	A+		
<b>Auxiliary electricity consumption</b>	Electrical consumption at nominal heat output	e <sub>lmax</sub>	0.096 kW		
	Electrical consumption at partial load heat output	e <sub>lmin</sub>	0.014 kW		
	Electrical consumption in standby mode	e <sub>lSB</sub>	0.000 kW		
<b>Sealed Chamber</b>	Appliance Type (tightness)	Type	CC50		

Observe the specific precautions for installation, assembly and maintenance indicated in the manual accompanying the product, and the national and local rules in force

**CADEL s.r.l.**  
 Via Martiri della Libertà, 74  
 31025 SANTA LUCIA DI PIAVE (TV)  
 Tel. 0438 1520200 - Fax 0438 73343  
 Partita IVA n. 02102170265  
 R.E.A. TV227665 - Reg. Soc. Trib. TV 188949

Santa Lucia di Piave, 02/10/25

Dassie Roberto (R&D Manager)