

## INFORMATION REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATIONS (EU) 2015/1185 - (EU) 2015/1186 (PRODUCT FICHE)

Models	RIVER IDRO 16 T2
Intended use of the product:	Mechanically fed roomheater fitted with a boiler burning wood pellets
Manufacturer	Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia
Trade mark	CADEL
AVCP system	System 3
Notified body	NB 0476
Test report number	2013634
Harmonised technical specification	EN 16510-1:2022 / EN 16510-2-6:2022

### ESSENTIAL CHARACTERISTICS

<b>Fuel</b>	Log wood, moisture content $\leq 25\%$			No	
	Compressed wood with moisture content $< 12\%$			Yes	
<b>Type of heat output/room temperature control (select one)</b>	Single stage heat output, no room temperature control			No	
	Two or more manual stages, no room temperature control			No	
	With mechanic thermostat room temperature control			No	
	With electronic room temperature control			No	
	With electronic room temperature control plus day timer			No	
	With electronic room temperature control plus week timer			Yes	
<b>Other control options (multiple selections possible)</b>	Room temperature control, with presence detection			No	
	Room temperature control, with open window detection			No	
	With distance control option			Yes	
<b>Performance - Emissions</b>	No	Symbol		Nominal power	Reduced power
	Carbon monoxide emissions (CO at 13% O <sub>2</sub> )	CO <sub>nom</sub>	CO <sub>part</sub>	100 mg/Nm <sup>3</sup>	150 mg/Nm <sup>3</sup>
	Emission of nitrogen oxides (NO <sub>x</sub> at 13% O <sub>2</sub> )	NO <sub>xnom</sub>	NO <sub>xpart</sub>	95 mg/Nm <sup>3</sup>	94 mg/Nm <sup>3</sup>
	Emission of organic gaseous compounds (OGC at 13% O <sub>2</sub> )	OGC <sub>nom</sub>	OGC <sub>part</sub>	2 mg/Nm <sup>3</sup>	3 mg/Nm <sup>3</sup>
	Particulate matter emissions (PM at 13% O <sub>2</sub> )	PM <sub>nom</sub>	PM <sub>part</sub>	13 mg/Nm <sup>3</sup>	18 mg/Nm <sup>3</sup>
<b>Performance - Power and efficiency</b>	Heating power to the environment	P <sub>nom</sub>	P <sub>part</sub>	16,1 kW	4,9 kW
	Heating power to the water	P <sub>wnom</sub>	P <sub>wpart</sub>	12,9 kW	3,4 kW
	Efficiency - Useful efficiency	$\eta_{nom}$	$\eta_{part}$	93 %	96 %
<b>Space heating efficiency</b>	Seasonal energy efficiency	$\eta_s$			90 $\eta_s$ [%]
	Energy efficiency index	EEL			132
	Energy efficiency class (A++ / G scale)	-			A++
<b>Auxiliary electricity consumption</b>	Electrical consumption at nominal heat output	el <sub>max</sub>		0.117 kW	
	Electrical consumption at partial load heat output	el <sub>min</sub>		0.076 kW	
	Electrical consumption in standby mode	el <sub>SB</sub>		0.002 kW	
<b>Sealed Chamber</b>	Appliance Type (tightness)	Type		BF	

Observe the specific precautions for installation, assembly and maintenance indicated in the manual accompanying the product, and the national and local rules in force

**CADEL** s.r.l.  
Via Martiri della Libertà, 74  
31025 SANTA LUCIA DI PIAVE (TV)  
Tel. 0438 1520200 - Fax 0438.73343  
Partita IVA 06210210265  
R.E.A. TV 227665 - Reg. Soc. Trib. TV 189048

Santa Lucia di Piave, 02/03/26

Dassie Roberto (R&D Manager)