**INFORMATION REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATIONS (EU) 2015/1185 - (EU) 2015/1186 (PRODUCT FICHE)**

| | |
|---|---|
| Models | SABA 14 |
| Intended use of the product: | Residencial space heating appliance fired by wood pellets |
| Manufacturer | Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia |
| Trade mark | PEGASO |
| AVCP system | System 3 |
| Notified body | NB 0051 |
| Test report number | CS20-0048537-01 |
| Harmonised technical specification | EN 14785:2006 |

## ESSENTIAL CHARACTERISTICS

| | | | | | |
|---|---|---|---|---|---|
| **Fuel** | Log wood, moisture content ≤ 25 % | | | No | |
| | Compressed wood with moisture content < 12 % | | | Yes | |
| **Type of heat output/room temperature control (select one)** | Single stage heat output, no room temperature control | | | No | |
| | Two or more manual stages, no room temperature control | | | No | |
| | With mechanic thermostat room temperature control | | | No | |
| | With electronic room temperature control | | | No | |
| | With electronic room temperature control plus day timer | | | No | |
| | With electronic room temperature control plus week timer | | | Yes | |
| **Other control options (multiple selections possible)** | Room temperature control, with presence detection | | | No | |
| | Rroom temperature control, with open window detection | | | No | |
| | With distance control option | | | Yes | |
| **Performance - Emissions** | No | Symbol | | Nominal power | Reduced power |
| | Carbon monoxide emissions (CO at 13% O2) | COnom | COpart | 247 mg/Nm³ | 186 mg/Nm³ |
| | Emission of nitrogen oxides (NOX at 13% O2) | NOxnom | NOxpart | 114 mg/Nm³ | 109 mg/Nm³ |
| | Emission of organic gaseous compounds (OGC at 13% O2) | OGCnom | OGCpart | 3 mg/Nm³ | 3 mg/Nm³ |
| | Particulate matter emissions (PM at 13% O2) | PMnom | PMpart | 15 mg/Nm³ | 19 mg/Nm³ |
| **Performance - Power and efficiency** | Heating power to the environment | Pnom | Ppart | 14,0 kW | 3,8 kW |
| | Heating power to the water | Pwnom | PWpart | / | / |
| | Efficiency - Useful efficiency | ηnom | ηpart | 89 % | 93 % |
| **Space heating efficiency** | Seasonal energy efficiency | ηs | | 85 ηs [%] | |
| | Energy efficiency index | EEI | | 125 | |
| | Energy efficiency class (A++ / G scale) | - | | A+ | |
| **Auxiliary electricity consumption** | Electrical consumption at nominal heat output | elmax | | 0.153 kW | |
| | Electrical consumption at partial load heat output | elmin | | 0.049 kW | |
| | Electrical consumption in standby mode | elSB | | 0.002 kW | |
| **Sealed Chamber** | Appliance Type (tightness) | Type | | CC50 | |

Observe the specific precautions for installation, assembly and maintenance indicated in the manual accompanying the product, and the national and local rules in force

CADEL s.r.l.
Via Martiri della Libertà, 74
31025 SANTA LUCIA DI PIAVE (TV)
Tel. 0438 1520200 - Fax 0438.73343
Partita IVA 03 2 0 2 1 8 0 2 6 5
R.E.A. TV 227665 - Reg. Soc. Trib. TV 185949

Santa Lucia di Piave, 04/06/20

Dassie Roberto (R&D Manager)