



INFORMATION REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATIONS (EU) 2015/1185 - (EU) 2015/1186 (PRODUCT FICHE)

Models	VERA 7.0 UP
Intended use of the product:	
Manufacturer	Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia
Trade mark	PEGASO
AVCP system	System 3
Notified body	NB 0051
Test report number	CS20-0056309-01
Harmonised technical specification	EN 14785:2006

ESSENTIAL CHARACTERISTICS

Fuel	Log wood, moisture content $\leq 25\%$				
	Compressed wood with moisture content $< 12\%$				
Type of heat output/room temperature control (select one)	Single stage heat output, no room temperature control		No		
	Two or more manual stages, no room temperature control		No		
	With mechanic thermostat room temperature control		No		
	With electronic room temperature control		No		
	With electronic room temperature control plus day timer		No		
	With electronic room temperature control plus week timer				
Other control options (multiple selections possible)	Room temperature control, with presence detection		No		
	Room temperature control, with open window detection		No		
	With distance control option				
Performance - Emissions	No	Symbol		Nominal power	Reduced power
	Carbon monoxide emissions (CO at 13% O ₂)	CO _{nom}	CO _{part}	42 mg/Nm ³	238 mg/Nm ³
	Emission of nitrogen oxides (NOX at 13% O ₂)	NO _{xnom}	NO _{xpart}	117 mg/Nm ³	140 mg/Nm ³
	Emission of organic gaseous compounds (OGC at 13% O ₂)	OGC _{nom}	OGC _{part}	1 mg/Nm ³	4 mg/Nm ³
	Particulate matter emissions (PM at 13% O ₂)	PM _{nom}	PM _{part}	15 mg/Nm ³	20 mg/Nm ³
Performance - Power and efficiency	Heating power to the environment	P _{nom}	P _{part}	7,0 kW	2,5 kW
	Heating power to the water	P _{wnom}	P _{wpart}	/	/
	Efficiency - Useful efficiency	η_{nom}	η_{part}	90 %	91 %
Space heating efficiency	Seasonal energy efficiency	η_s	86 η_s [%]		
	Energy efficiency index	EEL	126		
	Energy efficiency class (A++ / G scale)	-	A+		
Auxiliary electricity consumption	Electrical consumption at nominal heat output	e _{lmax}	0.049 kW		
	Electrical consumption at partial load heat output	e _{lmin}	0.023 kW		
	Electrical consumption in standby mode	e _{lSB}	0.002 kW		
Sealed Chamber	Appliance Type (tightness)	Type	CC50		

Observe the specific precautions for installation, assembly and maintenance indicated in the manual accompanying the product, and the national and local rules in force

CADEL s.r.l.
Via Martiri della Libertà, 74
31025 SANTA LUCIA DI PIAVE (TV)
Tel. 0438 1520200 - Fax 0438 73343
Partita IVA n. 02102170265
R.E.A. TV227665 - Reg. Soc. Trib. TV 188949

Santa Lucia di Piave, 23/12/20

Dassie Roberto (R&D Manager)