



Pellet stoves Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 8,5
Introduced thermal power (at max)	kW	9,5
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	85
Useful efficiency (at min-at max)	%	90 - 89
Heatable volume (at min-at max)	m ³	70 - 238
CO ₂ (min-max)	%	6,3 - 12,0
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	297 - 160
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	5,0 - 3,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	120 - 99
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	20 - 15
Fuel Pellet	mm	Ø6 L=3÷40
Hopper capacity	kg	17
Hourly consumption (at min-at max)	kg/h	0,6 - 2,0
Autonomy (at min-at max)	h	28 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	340
Operating electrical absorption (at max)	W	96
Draught for chimney sizing calculation (EN13384-1)	Pa	2
Mass of smoke (at min-at max)	g/sec	3,1 - 5,8
Exhaust fumes temperature (at min-at max)	°C	125 - 196
Distance from material comb. (back/side/under)	mm	200 / 300 / 15
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CC50

PLUS

- Airtight pellet stove
- Easy Start brazier
- Duo-Shield combustion chamber
- Integrated temperature sensor
- Connection to the external thermostat
- Silent
- Top and front ventilation
- Daily weekly programming

AVAILABLE FINISHES

7022008		Steel White	EAN 8053859014768
7022009		Steel Red Bordeaux	EAN 8053859014775
7022010		Steel Anthracite	EAN 8053859014782

OPTIONAL

5019012	Pellet stove remote control	EAN 8053859011965
---------	-----------------------------	-------------------

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 16510-1:2022 / EN 16510-2-6:2022
CE

A+

STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	118	61
	Volume (m ³)	0,58	
	Gross weight (kg)	79	
	Net weight (kg)	69	

STORAGE

	N° (max)
	2
MAX 2	
1	

TRANSPORT

66 pz