



Pellet Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 6,9
Introduced thermal power (at max)	kW	7,8
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	η_s [%]	85
Useful efficiency (at min-at max)	%	90 - 89
Heatable volume (at min-at max)	m ³	71 - 197
CO ₂ (min-max)	%	6,4 - 12,0
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	295 - 125
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	2,0 - 2,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	110 - 99
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	15 - 15
Fuel Pellet	mm	Ø6 L=3÷40
Hopper capacity	kg	32
Hourly consumption (at min-at max)	kg/h	0,6 - 1,6
Autonomy (at min-at max)	h	53 - 20
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	374
Operating electrical absorption (at max)	W	67
Draught for chimney sizing calculation (EN13384-1)	Pa	2
Mass of smoke (at min-at max)	g/sec	3,0 - 4,6
Exhaust fumes temperature (at min-at max)	°C	109 - 177
Distance from material comb. (back/side/under)	mm	40 / 250 / 0
Distance to material comb. (front/top)	mm	600 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CC50

PLUS

- 5 stars D.M. 186
- Upper, back and lateral exhaust
- Cast iron door
- Remote control (optional)
- Cast iron burning pot
- Connection to the external thermostat
- Comfort mode - Maximum silence
- Weekly programming

AVAILABLE FINISHES

7025091		Steel Black	EAN 8053859022015
7025092		Steel Titanium	EAN 8053859022022

OPTIONAL

5025001	Black feet	EAN 8053859022213
---------	------------	-------------------

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 16510-1:2022 / EN 16510-2-6:2022



STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	117	103
	Volume (m ³)	0,96	
	Gross weight (kg)	87	
	Net weight (kg)	75	

STORAGE

	N° (max)
	1
MAX 1	

TRANSPORT

39 pz