




Certificate model name: FLOS 7 WOOD T1



Wood stoves

TECHNICAL DATA

Thermic Power (at min-at max)	kW	0,0 – 7,0
Introduced thermal power (at max)	kW	8,4
Water useful power (at min-at max)	kW	– –
Seasonal energy efficiency	ηs [%]	74
Useful efficiency (at min-at max)	%	0 – 84
Heatable volume (at min-at max)	m³	0 – 196
CO ₂ (min-max)	%	0,0– 8,8
Emissions CO (13% O ₂) (at min-at max)	mg/Nm³	0 – 1250
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm³	0– 60
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm³	0 – 110
Dust content at 13% O ₂ (at min-at max)	mg/Nm³	0 – 30
Fuel Legna	mm	max L 500
Hopper capacity	kg	0
Hourly consumption (at min-at max)	kg/h	0,0 – 1,9
Autonomy (at min-at max)	h	0 – 0
Ignition electrical absorption	W	0
Operating electrical absorption (at max)	W	0
Chimney flue depression (at min-at max)	Pa	0 – 12
Mass of smoke (at min-at max)	g/sec	0,0 – 6,7
Exhaust fumes temperature (at min-at max)	°C	0 – 211
Distance from material comb. (back/side/under)	mm	250 / 320 / 130
Distance to material comb. (front/top)	mm	2000 / 750
Exhaust fumes outlet (A)	Ø mm	150
Combustion air inlet (B)	Ø mm	80
Ducting outlet (C)	Ø mm	0
Ductable up to	m	0
Appliance Type (tightness)	Type	CM

PLUS



Cast iron door



Upper and back exhaust



Top exhaust outlet / UP



Airtight pellet stove



Refractory combustion chamber



Anti-smoke valve

AVAILABLE FINISHES

7024013  Cast Iron Black EAN 8053859020660


CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen




A+

STOVE PACKAGE



L (cm)	H (cm)	P (cm)
80	96	71
Volume (m³)	0,55	
Gross weight (kg)	148	
Net weight (kg)	138	

STORAGE



N° (max)
2

TRANSPORT



57 pz