



Wood stoves ventilated

TECHNICAL DATA

Thermic Power (at min-at max)	kW	0,0 – 7,0
Introduced thermal power (at max)	kW	8,4
Water useful power (at min-at max)	kW	– –
Seasonal energy efficiency	ηs [%]	75
Useful efficiency (at min-at max)	%	0 – 85
Heatable volume (at min-at max)	m³	0 – 196
CO ₂ (min-max)	%	0,0– 8,8
Emissions CO (13% O ₂) (at min-at max)	mg/Nm³	0 – 1.250
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm³	0,0– 60,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm³	0 – 110
Dust content at 13% O ₂ (at min-at max)	mg/Nm³	0 – 30
Fuel Legna	mm	max L 500
Hourly consumption (at min-at max)	kg/h	0,0 – 1,9
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	0
Operating electrical absorption (at max)	W	20
Draught for chimney sizing calculation (EN13384-1)	Pa	12
Mass of smoke (at min-at max)	g/sec	0,0 – 6,7
Exhaust fumes temperature (at min-at max)	°C	0 – 211
Distance from material comb. (back/side/under)	mm	250 / 320 / 130
Distance to material comb. (front/top)	mm	2000 / 750
Exhaust fumes outlet (A)	Ø mm	150
Combustion air inlet (B)	Ø mm	80
Appliance Type (tightness)	Type	CM

PLUS

- Cast iron door
- Top exhaust outlet / UP
- Airtight pellet stove
- Refractory combustion chamber
- 5 stars V.AIR
- Anti-smoke valve
- Front ventilation v.air

AVAILABLE FINISHES

7024014

Cast Iron Black

EAN 8053859020707

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen

A +

STOVE PACKAGE

P	L
H	
L (cm)	H (cm)
80	96
P (cm)	71
Volume (m³)	0,55
Gross weight (kg)	150
Net weight (kg)	140

STORAGE

	N° (max)
MAX 2	2
1	

TRANSPORT

57 pz