



Wood-burning cookers

TECHNICAL DATA

Thermic Power (at min-at max)	kW	0,0 - 7,5
Introduced thermal power (at max)	kW	9,4
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	75
Useful efficiency (at min-at max)	%	0 - 86
Heatable volume (at min-at max)	m ³	0 - 214
CO ₂ (min-max)	%	0,0 - 9,6
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	0 - 1.167
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	0,0 - 69,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	0 - 85
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	0 - 20
Fuel Legna	mm	max L 330
Hourly consumption (at min-at max)	kg/h	0,0 - 2,1
Draught for chimney sizing calculation (EN13384-1)	Pa	12 - 12
Mass of smoke (at min-at max)	g/sec	0,0 - 7,1
Exhaust fumes temperature (at min-at max)	°C	0 - 203
Distance from material comb. (back/side/under)	mm	0+40 / 2,5 / 0
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	140
Combustion air inlet (B)	Ø mm	80
Appliance Type (tightness)	Type	BE

PLUS

- Cast iron combustion chamber
- Upper and back exhaust
- Stainless steel oven
- Cast iron cooktop
- Refractory combustion chamber
- Large drawer on guides

AVAILABLE FINISHES

71230160 Steel Black EAN 8053859019596

OPTIONAL

5021005 Connector pipe 140-150mm EAN 8053859014256

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 16510-1:2022 / EN 16510-2-3:2022
CE

A+

STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	102	98
Volume (m ³)			0,80
Gross weight (kg)			166
Net weight (kg)			152

STORAGE

	N° (max)
	1
MAX 1	

TRANSPORT

39 pz