



Pellet Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 6,9
Introduced thermal power (at max)	kW	7,8
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	85
Useful efficiency (at min-at max)	%	90 - 89
Heatable volume (at min-at max)	m³	71 - 197
CO ₂ (min-max)	%	6,4 - 12,0
Emissions CO (13% O ₂) (at min-at max)	mg/Nm³	295 - 125
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm³	2,0 - 2,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm³	110 - 99
Dust content at 13% O ₂ (at min-at max)	mg/Nm³	15 - 15
Fuel Pellet	mm	Ø6 L=3÷40
Hopper capacity	kg	12
Hourly consumption (at min-at max)	kg/h	0,6 - 1,6
Autonomy (at min-at max)	h	20 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	374
Operating electrical absorption (at max)	W	67
Draught for chimney sizing calculation (EN13384-1)	Pa	2 - 12
Mass of smoke (at min-at max)	g/sec	3,0 - 4,6
Exhaust fumes temperature (at min-at max)	°C	109 - 177
Distance from material comb. (back/side/under)	mm	40 / 250 / 0
Distance to material comb. (front/top)	mm	600 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CC50

PLUS

- 5 stars D.M. 186
- Upper, back and lateral exhaust
- Cast iron door
- Remote control (optional)
- Cast iron burning pot
- Connection to the external thermostat
- Comfort mode - Maximum silence
- Weekly programming

AVAILABLE FINISHES

7025073		Steel Anthracite	EAN 8053859021834
7025074		Steel White	EAN 8053859021841
7025075		Steel Red Bordeaux	EAN 8053859021858
7025076		Steel Light Bronze	EAN 8053859021865
7025077		Stone Serpetino	EAN 8053859021872

OPTIONAL

5019005	Pedestal support kit	EAN 8053859010951
5019009	Wall support kit	EAN 8053859011736

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 16510-1:2022 / EN 16510-2-6:2022
CE

STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	117	60
	Volume (m³)	0,56	
	Gross weight (kg)	73,5	
	Net weight (kg)	63,5	

STORAGE

	N° (max)
	2
MAX 2	
1	

TRANSPORT

	66 pz
--	-------