



# HUBLLOT 6 UP-TWIN

CADEL

Certificate model name: HUBLLOT 6 UP T1

www.cadelsrl.com



## Pellet Air

### TECHNICAL DATA

|                                                     |        |               |
|-----------------------------------------------------|--------|---------------|
| Thermic Power (at min-at max)                       | kW     | 2,8 - 6,0     |
| Introduced thermal power (at max)                   | kW     | 6,7           |
| Water useful power (at min-at max)                  | kW     | - -           |
| Seasonal energy efficiency                          | ηs [%] | 86            |
| Useful efficiency (at min-at max)                   | %      | 91 - 90       |
| Heatable volume (at min-at max)                     | m³     | 78 - 168      |
| CO <sub>2</sub> (min-max)                           | %      | 7,4 - 11,2    |
| Emissions CO (13% O <sub>2</sub> ) (at min-at max)  | mg/Nm³ | 150 - 100     |
| Emissions OGC (13%O <sub>2</sub> ) (at min-at max)  | mg/Nm³ | 1 - 1         |
| Emissions NOX (13% O <sub>2</sub> ) (at min-at max) | mg/Nm³ | 115 - 120     |
| Dust content at 13% O <sub>2</sub> (at min-at max)  | mg/Nm³ | 19 - 15       |
| Fuel Pellet                                         | mm     | Ø6 L=3÷40     |
| Hopper capacity                                     | kg     | 10            |
| Hourly consumption (at min-at max)                  | kg/h   | 0,7 - 1,4     |
| Autonomy (at min-at max)                            | h      | 14 - 7        |
| Supply and frequency                                | V-Hz   | 230-50        |
| Ignition electrical absorption                      | W      | 370           |
| Operating electrical absorption (at max)            | W      | 86            |
| Chimney flue depression (at min-at max)             | Pa     | 10 - 11       |
| Mass of smoke (at min-at max)                       | g/sec  | 2,9 - 4,3     |
| Exhaust fumes temperature (at min-at max)           | °C     | 130 - 186     |
| Distance from material comb. (back/side/under)      | mm     | 200 / 200 / 0 |
| Distance to material comb. (front/top)              | mm     | 1000 / 750    |
| Exhaust fumes outlet (A)                            | Ø mm   | 80            |
| Combustion air inlet (B)                            | Ø mm   | 130           |
| Ducting outlet (C)                                  | Ø mm   | 0             |
| Ductable up to                                      | m      | 0             |

### PLUS



4 stars +



Upper exhaust



Integrated concentric outlet (80-130 mm)



Go Fast - Faster pellet ignition



Sealed Chamber



Cast iron burning pot



Connection to the external thermostat



Cast iron inner



Weekly programming

### AVAILABLE FINISHES

7023038



Cast Iron Black

EAN 8053859019282

### OPTIONAL

5018013

Pellet loading chute kit

EAN 8053859010494

### CERTIFICATIONS

European standards  
Art. 15A B-VG 2015  
BlmSchV 2015  
Regensburg  
München  
Stuttgart  
Aachen


EN 16510-1:2022/  
EN 16510-2-6:2022

CE




A+

### STOVE PACKAGE



|                   |        |        |
|-------------------|--------|--------|
| L (cm)            | H (cm) | P (cm) |
| 80                | 91     | 71     |
| Volume (m³)       | 0,52   |        |
| Gross weight (kg) | 128    |        |
| Net weight (kg)   | 118    |        |

### STORAGE



N° (max)

2

### TRANSPORT



57 pz