



Pellet stoves Air

TECHNICAL DATA

| | | |
|---|--------------------|---------------|
| Thermic Power (at min-at max) | kW | 2,5 - 7,0 |
| Introduced thermal power (at max) | kW | 7,7 |
| Water useful power (at min-at max) | kW | - - |
| Seasonal energy efficiency | ηs [%] | 86 |
| Useful efficiency (at min-at max) | % | 91 - 90 |
| Heatable volume (at min-at max) | m ³ | 71 - 200 |
| CO ₂ (min-max) | % | 6,8 - 12,8 |
| Emissions CO (13% O ₂) (at min-at max) | mg/Nm ³ | 238 - 42 |
| Emissions OGC (13%O ₂) (at min-at max) | mg/Nm ³ | 4,0 - 1,0 |
| Emissions NOX (13% O ₂) (at min-at max) | mg/Nm ³ | 140 - 117 |
| Dust content at 13% O ₂ (at min-at max) | mg/Nm ³ | 20 - 15 |
| Fuel Pellet | mm | Ø6 L=3÷40 |
| Hopper capacity | kg | 15 |
| Hourly consumption (at min-at max) | kg/h | 0,6 - 1,7 |
| Autonomy (at min-at max) | h | 25 - 9 |
| Supply and frequency | V-Hz | 230-50 |
| Ignition electrical absorption | W | 345 |
| Operating electrical absorption (at max) | W | 49 |
| Draught for chimney sizing calculation (EN13384-1) | Pa | 2 |
| Mass of smoke (at min-at max) | g/sec | 2,6 - 4,6 |
| Exhaust fumes temperature (at min-at max) | °C | 113 - 190 |
| Distance from material comb. (back/side/under) | mm | 200 / 300 / 0 |
| Distance to material comb. (front/top) | mm | 1000 / 750 |
| Exhaust fumes outlet (A) | Ø mm | 80 |
| Combustion air inlet (B) | Ø mm | 60 |
| Appliance Type (tightness) | Type | CC50 |

PLUS

- Airtight pellet stove
- Easy Start brazier
- Duo-Shield combustion chamber
- Integrated temperature sensor
- Connection to the external thermostat
- Smart Heat
- Silent

AVAILABLE FINISHES

| | | | |
|---------|--|--------------------|-------------------|
| 7020008 | | Steel Anthracite | EAN 8053859011989 |
| 7020009 | | Steel Red Bordeaux | EAN 8053859011996 |
| 7020010 | | Steel White | EAN 8053859012009 |

OPTIONAL

| | | |
|---------|-----------------------------|-------------------|
| 5019012 | Pellet stove remote control | EAN 8053859011965 |
|---------|-----------------------------|-------------------|

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen

EN 14785:2006
CE



STOVE PACKAGE

| | | | |
|--|--------------------------|--------|--------|
| | L (cm) | H (cm) | P (cm) |
| | 80 | 117 | 60 |
| | Volume (m ³) | 0,56 | |
| | Gross weight (kg) | 65 | |
| | Net weight (kg) | 55 | |

STORAGE

| | |
|-------|----------|
| | N° (max) |
| | 2 |
| MAX 2 | |
| 1 | |

TRANSPORT

| |
|-------|
| |
| 66 pz |