

Pellet stoves Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 8,5
Introduced thermal power (at max)	kW	9,5
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	85
Useful efficiency (at min-at max)	%	90 - 89
Heatable volume (at min-at max)	m³	70 - 238
CO ₂ (min-max)	%	6,3 - 12,0
Emissions CO (13% O ₂) (at min-at max)	mg/Nm³	297 - 160
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm³	5,0 - 3,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm³	120 - 99
Dust content at 13% O ₂ (at min-at max)	mg/Nm³	20 - 15
Fuel Pellet	mm	Ø 6 L=3÷40
Hopper capacity	kg	17
Hourly consumption (at min-at max)	kg/h	0,6 - 2,0
Autonomy (at min-at max)	h	28 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	340
Operating electrical absorption (at max)	W	96
Draught for chimney sizing calculation (EN13384-1)	Pa	2
Mass of smoke (at min-at max)	g/sec	3,1 - 5,8
Exhaust fumes temperature (at min-at max)	°C	125 - 196
Distance from material comb. (back/side/under)	mm	200 / 300 / 15
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CC50

PLUS

-  Airtight pellet stove
-  Integrated Wi-Fi and Bluetooth
-  Connection to the external thermostat
-  Integrated temperature sensor
-  Smart Heat
-  Silent
-  Cast iron door

AVAILABLE FINISHES

7025018		Steel Black	EAN 8053859021261
7025020		Steel Titanium	EAN 8053859021285

OPTIONAL

5019012	Pellet stove remote control	EAN 8053859011965
5022001	Upper exhaust kit	EAN 8053859015536
5022003	Upper exhaust + concent kit	EAN 8053859015550

CERTIFICATIONS


European standards
Art. 15A B-VG 2015
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 15610-1:2022 / EN 15610-2-6:2022




STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	118	61
	Volume (m³)	0,58	
	Gross weight (kg)	88	
	Net weight (kg)	78	

STORAGE

	N° (max)
	2
MAX 2	
1	

TRANSPORT


66 pz