



Pellet Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,8 - 6,0
Introduced thermal power (at max)	kW	6,7
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	86
Useful efficiency (at min-at max)	%	91 - 90
Heatable volume (at min-at max)	m ³	78 - 168
CO ₂ (min-max)	%	7,4- 11,2
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	150 - 100
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	1,0- 1,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	115 - 120
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	19 - 15
Fuel Pellet	mm	Ø6 L=3÷40
Hopper capacity	kg	10
Hourly consumption (at min-at max)	kg/h	0,7 - 1,4
Autonomy (at min-at max)	h	14 - 7
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	370
Operating electrical absorption (at max)	W	86
Draught for chimney sizing calculation (EN13384-1)	Pa	2
Mass of smoke (at min-at max)	g/sec	2,9 - 4,3
Exhaust fumes temperature (at min-at max)	°C	130 - 186
Distance from material comb. (back/side/under)	mm	200 / 200 / 0
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CC50

PLUS

- 4 stars +
- Upper exhaust
- Back exhaust
- Go Fast - Faster pellet ignition
- Cast iron burning pot
- Connection to the external thermostat
- Cast iron inner
- Weekly programming
- Integrated Wi-Fi and Bluetooth

AVAILABLE FINISHES

7023037	● Cast Iron Black	EAN 8053859019275
---------	-------------------	-------------------

OPTIONAL

5018013	Pellet loading chute kit	EAN 8053859010494
---------	--------------------------	-------------------

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 16510-1:2022 / EN 16510-2-6:2022
CE

STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	94	71
	Volume (m ³)	0,53	
	Gross weight (kg)	136	
	Net weight (kg)	126	

STORAGE

	N° (max)
	2
MAX 2	1

TRANSPORT

57 pz