

Pellet stoves Air

TECHNICAL DATA

|                                                     |        |               |
|-----------------------------------------------------|--------|---------------|
| Thermic Power (at min-at max)                       | kW     | 2,9 - 7,0     |
| Introduced thermal power (at max)                   | kW     | 7,9           |
| Water useful power (at min-at max)                  | kW     | - -           |
| Seasonal energy efficiency                          | ηs [%] | 85            |
| Useful efficiency (at min-at max)                   | %      | 90 - 89       |
| Heatable volume (at min-at max)                     | m³     | 83 - 200      |
| CO <sub>2</sub> (min-max)                           | %      | 7,8 - 12,0    |
| Emissions CO (13% O <sub>2</sub> ) (at min-at max)  | mg/Nm³ | 220 - 125     |
| Emissions OGC (13%O <sub>2</sub> ) (at min-at max)  | mg/Nm³ | 2,0 - 2,0     |
| Emissions NOX (13% O <sub>2</sub> ) (at min-at max) | mg/Nm³ | 110 - 99      |
| Dust content at 13% O <sub>2</sub> (at min-at max)  | mg/Nm³ | 20 - 15       |
| Fuel Pellet                                         | mm     | Ø 6 L=3÷40    |
| Hopper capacity                                     | kg     | 15            |
| Hourly consumption (at min-at max)                  | kg/h   | 0,6 - 1,7     |
| Autonomy (at min-at max)                            | h      | 25 - 9        |
| Supply and frequency                                | V-Hz   | 230-50        |
| Ignition electrical absorption                      | W      | 350           |
| Operating electrical absorption (at max)            | W      | 74            |
| Draught for chimney sizing calculation (EN13384-1)  | Pa     | 2             |
| Mass of smoke (at min-at max)                       | g/sec  | 3,0 - 5,0     |
| Exhaust fumes temperature (at min-at max)           | °C     | 164 - 239     |
| Distance from material comb. (back/side/under)      | mm     | 200 / 300 / 0 |
| Distance to material comb. (front/top)              | mm     | 650 / 750     |
| Exhaust fumes outlet (A)                            | Ø mm   | 80            |
| Combustion air inlet (B)                            | Ø mm   | 60            |
| Appliance Type (tightness)                          | Type   | CC50          |

PLUS



Airtight pellet stove



Easy Start brazier



Duo-Shield combustion chamber



Connection to the external thermostat



Integrated temperature sensor



Integrated Wi-Fi and Bluetooth



Silent



Smart Heat

AVAILABLE FINISHES

|         |                                                                                     |                  |                   |
|---------|-------------------------------------------------------------------------------------|------------------|-------------------|
| 7025010 |  | Steel White      | EAN 8053859021186 |
| 7025011 |  | Steel Anthracite | EAN 8053859021193 |
| 7025012 |  | Steel Titanium   | EAN 8053859021209 |

CERTIFICATIONS

European standards  
Art. 15A B-VG 2015  
BlmSchV 2015  
Regensburg  
München  
Stuttgart  
Aachen


EN 16510-1:2022 / EN 16510-2-6:2022

CE



A+

STOVE PACKAGE



|                   |        |        |
|-------------------|--------|--------|
| L (cm)            | H (cm) | P (cm) |
| 80                | 117    | 60     |
| Volume (m³)       | 0,56   |        |
| Gross weight (kg) | 68     |        |
| Net weight (kg)   | 58     |        |

STORAGE




MAX 2

|          |
|----------|
| N° (max) |
| 2        |

1

TRANSPORT



66 pz