



Pellet stoves Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 7,0
Introduced thermal power (at max)	kW	7,7
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	86
Useful efficiency (at min-at max)	%	91 - 90
Heatable volume (at min-at max)	m ³	71 - 200
CO ₂ (min-max)	%	6,8 - 12,8
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	238 - 42
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	4,0 - 1,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	140 - 117
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	20 - 15
Fuel Pellet	mm	Ø6 L=3÷40
Hopper capacity	kg	15
Hourly consumption (at min-at max)	kg/h	0,6 - 1,7
Autonomy (at min-at max)	h	25 - 9
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	345
Operating electrical absorption (at max)	W	49
Draught for chimney sizing calculation (EN13384-1)	Pa	2
Mass of smoke (at min-at max)	g/sec	2,6 - 4,6
Exhaust fumes temperature (at min-at max)	°C	113 - 190
Distance from material comb. (back/side/under)	mm	200 / 300 / 0
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CC50

PLUS

- Airtight pellet stove
- Easy Start brazier
- Duo-Shield combustion chamber
- Connection to the external thermostat
- Integrated temperature sensor
- Smart Heat
- Silent

AVAILABLE FINISHES

7021002		Steel White	EAN 8053859013020
7021004		Steel Anthracite	EAN 8053859013044
7021005		Steel Titanium	EAN 8053859013051

OPTIONAL

5019012	Pellet stove remote control	EAN 8053859011965
---------	-----------------------------	-------------------

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 14785:2006
CE

A+

STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	117	60
Volume (m ³)			0,56
Gross weight (kg)			68
Net weight (kg)			58

STORAGE

	N° (max)
	2
MAX 2	
1	

TRANSPORT

66 pz