





Pellet Hydro

TECHNICAL DATA

Thermic Power (at min-at max)	kW	4,9 – 18,0
Introduced thermal power (at max)	kW	19,4
Water useful power (at min-at max)	kW	13,2 – 3,1
Seasonal energy efficiency	ηs [%]	90
Useful efficiency (at min-at max)	%	94 – 93
Heatable volume (at min-at max)	m³	137 – 504
CO ₂ (min-max)	%	7,0– 13,2
Emissions CO (13% O ₂) (at min-at max)	mg/Nm³	225 – 98
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm³	3,0– 1,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm³	95 – 98
Dust content at 13% O ₂ (at min-at max)	mg/Nm³	12 – 7
Fuel Pellet	mm	Ø6 L=3÷40
Boiler capacity (H ₂ O)	l	14
Hopper capacity	kg	26
Hourly consumption (at min-at max)	kg/h	1,0 – 4,0
Autonomy (at min-at max)	h	26 – 7
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	390
Operating electrical absorption (at max)	W	126
Draught for chimney sizing calculation (EN13384-1)	Pa	2
Mass of smoke (at min-at max)	g/sec	5,1 – 10,8
Exhaust fumes temperature (at min-at max)	°C	81 – 146
Distance from material comb. (back/side/under)	mm	200 / 200 / 0
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CM50

PLUS



AVAILABLE FINISHES

7026066		Steel Anthracite	EAN 8053859023401
7026065		Majolica White	EAN 8053859023395
7026067		Steel Light Bronze	EAN 8053859023418
7026068		Steel Titanium	EAN 8053859023425

OPTIONAL

5017002	Ntc probe wire	EAN 8053859015574
5017003	Boiler snubber module kit	EAN 8053859015581
5022004	Anticondensation valve kit	EAN 8053859015598

CERTIFICATIONS

European standards
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen




EN 16510-1:2022 / EN 16510-2-6:2022
CE

A++

STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	132	71
	Volume (m³)	0,75	
	Gross weight (kg)	146	
	Net weight (kg)	136	

STORAGE



TRANSPORT

