




Pellet Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 5,5
Introduced thermal power (at max)	kW	6,1
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	86
Useful efficiency (at min-at max)	%	91 - 90
Heatable volume (at min-at max)	m³	71 - 157
CO ₂ (min-max)	%	0,0- 11,7
Emissions CO (13% O ₂) (at min-at max)	mg/Nm³	238 - 140
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm³	4- 2
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm³	140 - 129
Dust content at 13% O ₂ (at min-at max)	mg/Nm³	20 - 15
Fuel Pellet	mm	Ø6 L=3÷40
Hopper capacity	kg	11
Hourly consumption (at min-at max)	kg/h	0,6 - 1,3
Autonomy (at min-at max)	h	18 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	345
Operating electrical absorption (at max)	W	50
Chimney flue depression (at min-at max)	Pa	10 - 12
Mass of smoke (at min-at max)	g/sec	2,6 - 3,9
Exhaust fumes temperature (at min-at max)	°C	113 - 163
Distance from material comb. (back/side/under)	mm	200 / 300 / 0
Distance to material comb. (front/top)	mm	650 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Ducting outlet (C)	Ø mm	0
Ductable up to	m	0

PLUS

Back exhaust	Magic Glass	Sealed Chamber
Cast iron burning pot	Connection to the external thermostat 1-2-3	Comfort mode - Maximum silence
Weekly programming 7	Integrated Wi-Fi and Bluetooth	Shield

AVAILABLE FINISHES

7025051		Steel Anthracite	EAN 8053859021605
---------	--	------------------	-------------------

CERTIFICATIONS

European standards
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 16510-1:2022/
EN 16510-2-6:2022
CE

STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	117	60
	Volume (m³)	0,56	
	Gross weight (kg)	83	
	Net weight (kg)	73	

STORAGE

	N° (max)
	2
MAX 2	
1	

TRANSPORT

66 pz