




SPIN 8 WOOD AIR

CADEL

Certificate model name: SPIN 8 WOOD AIR T1

www.cadelsrl.com



Wood Air stoves

TECHNICAL DATA

Thermic Power (at min-at max)	kW	0,0 - 8,0
Introduced thermal power (at max)	kW	9,5
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	η_s [%]	74
Useful efficiency (at min-at max)	%	0 - 84
Heatable volume (at min-at max)	m ³	0 - 224
CO ₂ (min-max)	%	0,0 - 8,4
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	0 - 990
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	0 - 50
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	0 - 99
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	0 - 25
Fuel Legna	mm	max L 330
Hopper capacity	kg	0
Hourly consumption (at min-at max)	kg/h	0,0 - 2,2
Autonomy (at min-at max)	h	0 - 0
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	0
Operating electrical absorption (at max)	W	20
Chimney flue depression (at min-at max)	Pa	0 - 10
Mass of smoke (at min-at max)	g/sec	0,0 - 7,6
Exhaust fumes temperature (at min-at max)	°C	0 - 230
Distance from material comb. (back/side/under)	mm	200 / 350 / 0
Distance to material comb. (front/top)	mm	1200 / 800
Exhaust fumes outlet (A)	Ø mm	150
Combustion air inlet (B)	Ø mm	80
Ducting outlet (C)	Ø mm	0
Ductable up to	m	0

PLUS



5 stars D.M. 186



Upper exhaust



Refractory stone



Ventilation



Sealed Chamber

AVAILABLE FINISHES

7025113



Cast Iron Black


EAN 8053859022282

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen




STOVE PACKAGE




L (cm)	H (cm)	P (cm)
80	126	68
Volume (m ³)	0,69	
Gross weight (kg)	165	
Net weight (kg)	153	

STORAGE



N° (max)
2

TRANSPORT



60 pz